



Installation

Model specific instructions

For:

- Yamaha XV 950 Bolt
- Yamaha XV 950 R Bolt
- Yamaha XV 950 Racer
- Yamaha SCR 950

These instructions are a model specific add-on to the general BoosterPlug installation instructions.

The general BoosterPlug installation instructions can be found in the "Downloads" section on the BoosterPlug.com website:

<http://www.boosterplug.com/shop/cms-downloads.html>

Installation Tips

- Install the BoosterPlug module as per the general installation papers.
- The picture below should help you locate the AIT sensor where the BoosterPlug is installed.
 - **Please note that the AIT sensor can be a bit hard to find, but it is definitely there :-)**
 - **Use a flashlight and look behind the head light - under the top triple clamp on the front fork.**
- On the XV 950 bikes, the AIT sensor is located on a small bracket, just behind the head light.
 - To access the AIT sensor you must remove the bracket by undoing a single bolt (Pictures on the left side below)
 - You may find it easier to remove the head light to get to the AIT sensor.
- On the SCR 950 bikes, the AIT sensor is located behind the head light.
 - You must remove the two bolts holding the head light to access the AIT sensor
- AIT sensor marked with a red circle on the right hand side picture.
- The External sensor on the BoosterPlug is already in the right spot, so you just need to secure it with a zip-tie to avoid it from flopping around.

Pictures

For:

- Yamaha XV 950 Bolt
- Yamaha XV 950 R Bolt
- Yamaha XV 950 Racer



For:

- Yamaha SCR 950

